

SWE35UF Mini Excavator

Operating Weight: 8,490 LBS (3,850 KG)

Gross Power: 24.8 HP (18.5 kW)

Dig Depth: 10' 3" (3.12 m)



Turn
over for full
specifications!

Technical Specifications and Product Highlights

Machine Weight		8,490 lbs	3,850 kg
Machine Dimensions	Overall Length	16'	4.89 m
	Overall Height	8' 4"	2.545 m
	Overall Width	5' 7"	1.7 m
	Ground Clearance	11"	270 mm
	Tail Swing Radius	2' 8"	.85 m
Engine	Brand	KUBOTA	
	Model	D1703-E4B-SWD-1	
	Displacement	.44 Gal	1.647 L
	Output	24.8 HP	18.5 kW
	Max Speed (High/Low)	2.6 / 1.4 mph	4.2 / 2.3 kph
Working Ranges	Max Cutting Height	16' 2"	4.925 m
	Max Loading Height	11' 2"	3.4 m
	Max Digging Depth	10' 3"	3.12 m
	Max Vertical Digging Depth	17' 3"	5.26 m
	Max Digging Reach	17' 8"	5.390 m
	Boom Swing Angle (Left/Right)	74 / 44	
	Front Swing Radius	7' 5"	2.263 m
	Tail Swing Radius	2' 9"	.85 m
	Max Digging Force (Arm)	5.1 kip	22.53 kN
	Max Digging Force (Bucket)	7.1 kip	31.8 kN
	Dozer Blade Height x Width	1' 3" x 5' 7"	.381 m x 1.7 m
	Swing Speed	9 rpm	
	Ground Pressure	4.69 psi	32.3 kpa
	Tracks	Track Width	11.8 in
Track Height		1' 6"	.45 m
Track Type		Rubber Crawler	
Gradeability		30 Degrees	
Hydraulics	Brand	KYB	
	Type	1 Variable Plunger Pumps	
	Total Flow	23.2 gal/min	88 L/min
	Pressure	3,553 psi	24.5 Mpa
Fuel and Hydraulics Tanks	Fuel Tank Capacity	10.6 Gal	40 L
	Hydraulic Oil Capacity	10.8 Gal	41 L



Zero-Tail Swing



Kubota Engine with easy access panels for maintenance



Enclosed cab offers A/C, Touch Monitor, and removable windshield and windows for comfort and visibility

Advanced touch-panel monitor

- 1 self-diagnosis
- 2 fuel level
- 3 engine speed
- 4 working voltage
- 5 working hours
- 6 water temperature
- 7 function selection

Sunward USA Corp

Web: www.sunwardusa.com

Address: 2710 Geesling Rd, Denton TX 76208

Contact Info

Phone: (469)-353-6890

Email: info@sunwardusa.com

Model:

SWE35UF